

FLOATER GUM



Product descriptions

REF No.	MODEL No.	DESCRIPTION
29002	FL-02	2kg 0.8mm × 500mm × about 3.8m
29005	FL-05	5kg 0.8mm × 500mm × about 9.5m

Properties

- Cushion gum for the bonding layer of the MR, MB and MS tire patches.
- Absorbs shocks from the tire to prevent splitting, breakage and wear on the patch which ensures long-lasting repairs.
- Use in combination with patches to improve adhesion strength during the attachment process.
- Facilitates adhesion of larger sized patches.
- Use with SUPER VALKARN G / CFC FREE for self-vulcanizing adhesion with the tire and patch.
- Can be used for both cold and hot curing.
- Shelf life: 2 years at 20°C when direct sunlight and humidity are avoided.

-
1. SELF VULCANIZING (Floater Gum + Tire-Patch) more than 24 hours at 20°C, more than 48 hours at 10°C
 2. LOW HEAT PRESSURE (Floater Gum + Tire-Patch) 30 min.~10hours at 90°C~110°C
 3. HIGH HEAT PRESSURE (Floater Gum + Tire-Patch + Filler Gum) 60min.~20 hours at 130°C 30min.~20 hours at 150°C
20min.~8 hours at 165°C